

HIGH TEMP SILICONE



Rubber Sheet Roll

Technical Data Sheet

COLOR	ORANGE, RED OR BLACK
SURFACE	SMOOTH
TEMP RANGE	- 60° F TO 525° F
TENSILE	1000 PSI
DUROMETER	50A NOMINAL
ELONGATION	300 %
FIRE RATED	NO
UV RATED	VERY GOOD
CHEMICAL RESISTENT	EXCELLENT
COMPOSITION	SYNTHETIC

PSA DATA

THICKNESS	5 MILS
SURFACE	RELEASE LINER ONE SIDE
TEMPERATURE	300° F
COMPOSITION	SILICONE
FDA	NO

Description

High temperature silicone sheeting is designed to be used in applications where very extreme temperatures are required for extended periods of time. This material is Extreme High & Low Temperature Resistant, has great UV / Ozone Resistance, Non- Toxic, Chemically Inert, Low Compression Set and is Fungus Resistant.

Rubber Sheet Roll Shippensburg, PA 17257
 Phone: 866.832.6006
info@rubbersheetroll.com www.rubbersheetroll.com

HIGH TEMP SILICONE

All values given are averages based on test samples and the data given is based on what we have determined to be reliable. As results cannot be predicted or guaranteed for any specific set of conditions, each user should make their own determination of these products suitability for their particular application. **Viton® is a registered trademark of DuPont Performance Elastomers.**