



Rubber Sheet Roll

Technical Data Sheet

COLOR	BLACK
SURFACE	SMOOTH
TEMP RANGE	- 30° F TO 200° F
TENSILE	800 PSI
DUROMETER	60 A NOMINAL
ELONGATION	400 %
FIRE RATED	NO
UV RATED	EXCELLENT
CHEMICAL RESISTENT	EXCELLENT
COMPOSITION	SYNTHETIC

PSA DATA

THICKNESS	5 MILS
SURFACE	RELEASE LINER ONE SIDE
TEMPERATURE	250° F
COMPOSITION	ACRYLIC
FDA	NO

Description

EPDM Rubber resists elevated levels of ozone, high temperature water environments, petrochemicals and mild to extreme weather. Commercial Grade EPDM remains flexible as sheeting when subjected to harsh extremes like marine and underwater applications

Rubber Sheet Roll Shippensburg, PA 17257

Phone: 866.832.6006

info@rubbersheetroll.com www.rubbersheetroll.com

All values given are averages based on test samples and the data given is based on what we have determined to be reliable. As results cannot be predicted or guaranteed for any specific set of conditions, each user should make their own determination of these products suitability for their particular application. **Viton®** is a registered trademark of DuPont Performance Elastomers.

EPDM RUBBER

EPDM RUBBER